

Data Sheet

Fujitsu PRIMERGY TX2550 M7 Tower Server

The ultimate powerhouse at your feet

Fujitsu offers a fantastic blend of systems, solutions and expertise to guarantee maximum productivity, efficiency and flexibility, delivering confidence and reliability. Fujitsu Server PRIMERGY systems deliver workload-optimized x86 industry standard servers for any workload and business demand. Since there is no single server solution to meet all these needs, Fujitsu offers a broad server portfolio consisting of expandable tower servers for remote and branch offices, versatile rack-mount servers and density-optimized multi-node servers. Whatever the size of your business – large enterprise with multiple sites, or a small or medium-sized company with limited space and budget – with the right choice of server, your IT can become the business enabler you have always wanted it to be.

PRIMERGY TX2550 M7

The Fujitsu PRIMERGY Server TX2550 M7 is our small powerhouse among the tower servers. Equipped with the latest 4th generation Intel processors, the server offers outstanding performance and is therefore ideal for compute-intensive business processes, applications or virtual work environments. Improving efficiency, increasing performance and reducing power consumption at the same time is possible with the latest generation of DDR5 memory. These come with a significantly higher speed of up to 4,800 MT/s and enable a maximum capacity of up to 4TB with 4UPI links in the tower server, making it ideal for CPU-driven work processes. The TX2550 M7 offers space for up to 32x 2.5" SAS/SATA/NVME storage media, which can be easily exchanged thanks to Fujitsu hot-plug frames. Because of the easy scalability, companies are flexible and can start small and adapt the storage to their needs with HDDs or SSDs. On board there are 6 PCIe slots which can be expanded to 10 PCIe slots by means of a raiser card and can therefore be adapted to the needs of companies. Through the PCIe slots up

to 4 full height double width GPGPU cards can be added and the TX2550 offers an unprecedented computing performance in the segment of footprint servers.

The server is designed for quiet operation and offers best-in-class reliability and energy efficiency with up to 96% efficiency and dual power supplies. Fujitsu iRMC S6 and ISM increase administrator productivity and provide a fast path to infrastructure management.



Features & Benefits

Main Features	Benefits
<p>Power packed performance across workloads</p> <ul style="list-style-type: none"> Wide choice of different types of Intel® Xeon® Scalable processors as well as the new 4th generation Intel® Xeon® Scalable processors. The server can field CPUs with up to 32 cores relying on Intel® UltraPath Interconnect for an increased data rate between the CPUs. Up to 4TB memory (16 DIMM slots) including the new DDR5 modules with a bandwidth of 4,800 MT/s. <p>Highly expandable and flexible design</p> <ul style="list-style-type: none"> Significant storage capacity with up to 32x hot plug 2.5"SAS/SATA/NVMe for ODD or backup. Advanced RAID controllers with up to 8GB cache for enhanced data protection and reliability beyond embedded basic RAID capability. Flexibility in networking capability via Onboard LAN for basic requirements. <p>Designed to be upgrade ready and efficient</p> <ul style="list-style-type: none"> With optional riser card up to 10 PCIe slots are possible with the TX2550 M7. The extension makes it possible to add up to 4 full height double width GPU cards. Fields power supply units with 96% energy efficiency, plus Fujitsu's Cool-safe® Advanced Thermal Design for higher ambient temperatures in the data center. <p>Server and infrastructure management at your fingertips</p> <ul style="list-style-type: none"> The server also has regular, free updates of BIOS, firmware and selected software. The onboard iRMC S6 comes with interactive web UI and conforms to Redfish providing unified API support for heterogeneous environment. Furthermore, 2x Internal M.2 devices support hypervisor installations or mirroring while TPM2.0 modules enhance security. 	<ul style="list-style-type: none"> The enhanced dual-socket calculator and high bandwidth DDR5 processor help to improve efficiency and increase performance while reducing power consumption. The TX2550 M7 is capable of handling a range of different tasks at the highest level: demanding industrial and analytical applications, business processes and enterprise applications, and virtualised workloads. Storage suitable for securely managing extremely large datasets and flexible enough to be matched to a range of storage centric requirements such as IT infrastructure or collaboration workloads. Drives and RAID controllers can be tailored to specific business needs and budgets. Powerful and cost-effective networking options are available depending on your business need and budget. Versatile PCIe slots offer flexible expandability for the integration of existing and new storage controllers, networking cards, or the benefits of graphic cards. Add capabilities per your business needs. Graphics card improves performance for graphic intensive apps; get more from your display infrastructure. The server is designed for quiet operation and offers best-in-class reliability and energy efficiency with up to 96% efficiency and dual power supplies. The rack upgrade kit allows you to invest in a system designed for scalability to match your business growth. The onboard iRMC S6, is optimized for both data centers and SMEs who can rely on the latest generation server management. With ISM centralize the data center management as well as power and cooling by using a single user interface. Improve the whole data center productivity with converged infrastructure management. M.2 devices are perfect for hassle-free hypervisor / operating system start-up, while TPM 2.0 provides ease of mind for administrators with the latest hardware and Software driven security features.

Technical details

PRIMERGY TX2550 M7

Base unit	TX2550 M7 Rack SFF	TX2550 M7 Rack LFF	TX2550 M7 Rack SFF	TX2550 M7 Tower SFF	TX2550 M7 Tower LFF	TX2550 M7 Tower LFF	TX2550 M7 Tower SFF	TX2550 M7 Tower SFF
Housing types	Rack	Rack	Rack	Tower	Tower	Tower	Tower	Tower
Storage drive architecture	8x 2.5-inch SAS/SATA/PCIe expandable	8x 3.5-inch SAS/SATA expandable	24x 2.5-inch SAS/SATA/PCIe expandable	8x 2.5-inch SAS/SATA	4x 3.5-inch SAS/SATA expandable	8x 3.5-inch SAS/SATA expandable	8x 2.5-inch SAS/SATA/PCIe expandable	24x 2.5-inch SAS/SATA/PCIe expandable
Power supply	Hot-plug	Hot-plug	Hot-plug	Hot-plug	Hot-plug	Hot-plug	Hot-plug	Hot-plug
Product Type	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Rack Server	Dual Socket Tower Server	Dual Socket Tower Server	Dual Socket Tower Server	Dual Socket Tower Server	Dual Socket Tower Server

Mainboard

Mainboard type	D3985-A
Chipset	Intel® C741
Processor quantity and type	1 - 2 x Intel® Xeon® Bronze 3xxx processor / Intel® Xeon® Silver 4xxx processor / Intel® Xeon® Gold 5xxx processor / Intel® Xeon® Gold 6xxx processor / Intel® Xeon® Platinum 8xxx processor

Intel® Xeon® Bronze Processor Intel® Xeon® Bronze 3408U (8C, 1.8 GHz, TLC: 22.5 MB, Turbo: 1.90 GHz, 16 GT/s, Mem bus: 4,000MHz, 125 W)

Intel® Xeon® Silver Processor Intel® Xeon® Silver 4410T (10C, 2.7 GHz, TLC: 26.25 MB, Turbo: 3.40 GHz, 16 GT/s, Mem bus: 4,000MHz, 150 W)
Intel® Xeon® Silver 4410Y (12C, 2.0 GHz, TLC: 30 MB, Turbo: 2.90 GHz, 16 GT/s, Mem bus: 4,000MHz, 150 W)
Intel® Xeon® Silver 4416+ (20C, 2.0 GHz, TLC: 37.5 MB, Turbo: 2.90 GHz, 16 GT/s, Mem bus: 4,000MHz, 165 W)

Intel® Xeon® Gold Processor Intel® Xeon® Gold 5412U (24C, 2.1 GHz, TLC: 45 MB, Turbo: 2.90 GHz, 16 GT/s, Mem bus: 4,400MHz, 185 W)
Intel® Xeon® Gold 5415+ (8C, 2.9 GHz, TLC: 22.5 MB, Turbo: 3.60 GHz, 16 GT/s, Mem bus: 4,400MHz, 150 W)
Intel® Xeon® Gold 5416S (16C, 2.0 GHz, TLC: 30 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,400MHz, 150 W)
Intel® Xeon® Gold 5418Y (24C, 2.0 GHz, TLC: 45 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,400MHz, 185 W)
Intel® Xeon® Gold 5420+ (28C, 2.0 GHz, TLC: 52.5 MB, Turbo: 2.70 GHz, 16 GT/s, Mem bus: 4,400MHz, 205 W)
Intel® Xeon® Gold 6414U (32 C, 2.0 GHz, TLC: 60 MB, Turbo: 2.60 GHz, 16 GT/s, Mem bus: 4,800MHz, 250 W)
Intel® Xeon® Gold 6426Y (16C, 2.5 GHz, TLC: 37.5 MB, Turbo: 3.30 GHz, 16 GT/s, Mem bus: 4,800MHz, 185 W)
Intel® Xeon® Gold 6430 (32 C, 2.1 GHz, TLC: 60 MB, Turbo: 3.00 GHz, 16 GT/s, Mem bus: 4,400MHz, 270 W)
Intel® Xeon® Gold 6434 (8C, 3.7 GHz, TLC: 22.5 MB, Turbo: 4.10 GHz, 16 GT/s, Mem bus: 4,800MHz, 195 W)
Intel® Xeon® Gold 6438Y+ (32 C, 2.0 GHz, TLC: 60 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,800MHz, 205 W)
Intel® Xeon® Gold 6442Y (24C, 2.6 GHz, TLC: 60 MB, Turbo: 3.30 GHz, 16 GT/s, Mem bus: 4,800MHz, 225 W)
Intel® Xeon® Gold 6448Y (32 C, 2.1 GHz, TLC: 60 MB, Turbo: 3.00 GHz, 16 GT/s, Mem bus: 4,800MHz, 225 W)
Intel® Xeon® Gold 6454S (32 C, 2.2 GHz, TLC: 60 MB, Turbo: 2.80 GHz, 16 GT/s, Mem bus: 4,800MHz, 270 W)

Intel® Xeon® Platinum Processor Intel® Xeon® Platinum 8444H (16C, 2.9 GHz, TLC: 45 MB, Turbo: 3.20 GHz, 16 GT/s, Mem bus: 4,800MHz, 270 W)
Intel® Xeon® Platinum 8450H (28C, 2.0 GHz, TLC: 75 MB, Turbo: 2.60 GHz, 16 GT/s, Mem bus: 4,800MHz, 250 W)

Memory slots	16 (8 DIMMs per CPU, 8 channels with one DIMM per channel)
Memory slot type	DIMM (DDR5)
Memory capacity (min. - max.)	16 GB - 4.0 TB
Memory protection	ECC Memory Scrubbing SDDC ADDDC (Adaptive Double DRAM Device Correction) Memory Mirroring support
Memory notes	Independent Mode with identical modules in both channel pairs of a bank (1, 2, 4, 6 or 8 modules per bank) per CPU. Memory Mirroring Mode with identical modules in both channel pairs of a bank (8 modules per bank) per CPU.

Standard memory modules	16 GB (1 module(s) 16 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 1Rx8
	32 GB (1 module(s) 32 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 1Rx4
	32 GB (1 module(s) 32 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 2Rx8
	64 GB (1 module(s) 64 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 2Rx4
	128 GB (1 module(s) 128 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 4Rx4
256 GB (1 module(s) 256 GB) DDR5, registered, ECC, 4,800 MT/s, PC5-4800, DIMM, 8Rx4	

Interfaces

USB 3.x ports	8 x USB 3.1 Gen1(USB3.0) (2x front, 4 x rear, 2x internal (type A) for Backup(1)/Micro SD(1))
Graphics (15-pin)	1 x VGA(1 x rear, 1 x front(Optional))
Serial 1 (9-pin)	1 x optional serial RS-232-C (9 pin)(Optional, not shown)
LAN / Ethernet (RJ-45)	2 x
Management LAN (RJ45)	Management LAN traffic can be switched to shared onboard LAN port 1 x dedicated management LAN port for iRMC S6 (10/100/1000 Mbit/s)

Onboard or integrated Controller

RAID controller	All hardware storage controller options are described under Components
SATA Controller	Intel® C741, 1x SATA channel for ODD, 2x SATA channel for M.2, 8x SATA channel for HDD/SSD
SATA controller type notes	On Board SATA controller
LAN Controller	2 x 1 Gbit/s onboard
Remote management controller	IPMI 2.0 compatible Integrated Remote Management Controller (iRMC S6, 1024 MB attached memory incl. graphics controller)
Trusted Platform Module (TPM)	optional TPM

Slots

PCI-Express 5.0 x8	8 x Note: Refer to Slot Notes
PCI-Express 5.0 x16	6 x Full height
PCI-Express 4.0 x8	8 x Full height Note: Refer to Slot Notes.
PCI-Express 4.0 x16	4 x Full height Note: Refer to Slot Notes.
Slot Notes	Note: Slots: 6x PCIe slots are on board, with optional riser card up to 10x PCIe slots are available.

Drive bays

Storage drive bays	3.5-inch or 2.5-inch hot-plug SAS/SATA
Accessible drive bays	3 x 5.25/1.6-inch
Notes accessible drives	All possible options described in relevant system configurator.

Drive bays (Base unit specific)

Storage drive bays	8 x 2.5-inch hot-plug SAS/SATA	8 x 3.5-inch hot-plug SAS/SATA	24 x 2.5-inch hot-plug SAS/SATA	8 x 2.5-inch hot-plug SAS/SATA	4 x 3.5-inch hot-plug SAS/SATA	8 x 3.5-inch hot-plug SAS/SATA	8 x 2.5-inch hot-plug SAS/SATA	24 x 2.5-inch hot-plug SAS/SATA
Storage drive bay configuration	Optional expandable up to 24 storage drives	Optional expandable up to 12 storage drives	optional expanderble up to 32 storage drives	not expandable	optional expandable up to 8 storage drives	optional expandable up to 12 storage drives	optional expandable up to 24 storage drives	optional expandable up to 32 storage drives
Optional accessible drives	3x 1.6x5.25" bays for an optical and/or backup drives	3x 1.6x5.25" bays for an optical and/or backup drives	3x 1.6x5.25" bays for an optical and/or backup drives	3x 1.6x5.25" bays for an optical and/or backup drives	3x 1.6x5.25" bays for an optical and/or backup drives	3x 1.6x5.25" bays for an optical and/or backup drives	3x 1.6x5.25" bays for an optical and/or backup drives	3x 1.6x5.25" bays for an optical and/or backup drives

Fan Configuration

Number of fans	4
Fan configuration	4x92mm high power fans (single hot plug red.)
Fan notes	Fans with optimized blades and fan control for silent and safe operation

Operating panel

Operating buttons	On/off switch NMI button Reset button ID button
-------------------	--

Operating panel

Status LEDs	At system front side: Power (DC-On: green / AC-On: white) Global error (orange) Identification (blue) Hard disks access (green) System status (green) At system rear side: Identification (blue) CSS (orange) Global error (orange) LAN connection (green) LAN speed (green / yellow)
Service display	Optional: ServerView Local Service Display (LSD)

BIOS

BIOS features	UEFI compliant Secure boot support ROM based setup utility GPT support for boot drives larger than 2.2 TB Memory Redundancy support (Mirroring) IPMI support Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Linux versions Local and remote update via ServerView Update Manager IPv4/IPv6 remote PXE & iSCSI boot support Cryptographically Signed BIOS Firmware Update HTTP and HTTPS Boot PCIe Bifurcation configurable
---------------	---

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Windows Server 2022 Datacenter Windows Server 2022 Standard Windows Server 2019 Datacenter Windows Server 2019 Standard Windows Server 2019 Essentials SUSE® Linux Enterprise Server 15 Red Hat® Enterprise Linux 8
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
Operating system notes	Use of certified or supported operating systems and virtualization software is subject to proactive acceptance of the respective License Agreements/ EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.

Server Management

DC Infrastructure Management	Infrastructure Manager (ISM) Essential Edition Advanced Edition
Server Management	Infrastructure Manager (ISM) Essential Edition Advanced Edition ServerView Suite
Management notes	For further information regarding ISM and ServerView Suite see dedicated data sheets.
Manageability link	http://docs.ts.fujitsu.com/dl.aspx?id=9e92297a-16fb-4c69-8559-e38e7b42fee6

Dimensions / Weight

Floor-stand (W x D x H)	176 x 777 x 455 mm
Rack (W x D x H)	485 (Bezel); 448 mm (body) x 765 x 176 mm

Dimensions / Weight

Dimension notes	Floorstand Width 176 mm without tilt protection (483 mm with tilt protection); depth measured includes handles on redundant PSU. Rack depth includes handles of redundant PSU, excludes rack handles / front				
Height Unit Rack	4 U				
Weight	Up to 41.86 kg				
Weight notes	Actual weight may vary depending on configuration				
Rack integration kit	with retrofit upgrade.				
Floor-stand (W x D x H)					
Rack integration kit	Rack mount option available as a retrofit upgrade	Rack mount option available as a retrofit upgrade	Rack mount options available from the factory or with retrofit upgrade	Rack mount options available from the factory or with retrofit upgrade	Rack mount options available from the factory or with retrofit upgrade

Environment

Operating ambient temperature	5 - 45 °C (41 - 113 °F)				
Operating temperature note	Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. Please use the Fujitsu WebArchitect (www.fujitsu.com/configurator/public) to get detailed information on the corresponding configurations.				
Operating relative humidity	8 - 85 % (non condensing)				
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)				
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe				
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296				
Sound pressure (LpAm)	Noise minimum configuration: 26 dB(A) (idle) / 26 dB(A) (operating) Noise typical configuration: 26 dB(A) (idle) / 29 dB(A) (operating)				
Sound power (LWAd; 1B = 10dB)	Noise minimum configuration: 3.9 B (idle) / 4.0 B (operating) Noise typical configuration: 4.1 B (idle) / 4.8 B (operating)				
Noise notes	Noise emissions depends on operation modes, system configuration and ambient temperature. Operating mode measured based on OLTIS with 50% load. *OLTIS = FUJITSU Load Profile which stresses all components of a server with a given load level.				

Electrical values

Power supply configuration	1x non hot-plug power supply or 2x hot-plug power supply for redundancy or 2x non hot-plug power supply				
Hot-plug power supply redundancy	Optional				
Active power (max. configuration)	2,758 W				
Apparent power (max. configuration)	2790 VA				
Heat emission (max. configuration)	9928.8 kJ/h (9410.7 BTU/h)				
Rated current max.	12 A (100 V) / 15 A (200 V)				
Active power note	To estimate the power consumption of different configurations use the Fujitsu Product Configurator: www.fujitsu.com/configurator/public				
Power supply	500W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 500W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz 900W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 900W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz 1600W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz; 100V range: 1030W 1600W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz 2200W hot-plug, 94% (Platinum efficiency), 200-240V, 50 / 60Hz ; 100V range: 1000W 2400W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz				
Power supply notes	Power Safeguard adapts system performance in case the power requirements exceeds supply limits. Platinum PSUs are only for APAC/Japan market. 96% Titanium Power supply unit is only released for 200-240V This system supports no redundancy on 2x PSUs. The system Max. power has 4800 W possibility(T.B.D.)				

Compliance

Product	PRIMERGY TX2550 M7				
Model	PS2560A				
Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment)				
Germany	GS				

Compliance	
Europe	CE
USA/Canada	NRTLc/us FCC Class A ICES-003 / NMB-003 Class A
Japan	VCCI:V3 Class A + JIS 61000-3-2
Russia	EAC
South Korea	KC
China	CCC
Australia/New Zealand	RCM
Taiwan	BSMI
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Components

Backup Drives	LTO7HH Ultrium, 2,500 GB, 300 MB/s, half height, SAS 6Gb/s
	LTO7HH Ultrium, 300 MB/s, half height
	LTO7HH Ultrium, 300 MB/s, half height, SAS 6Gb/s
	RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0
Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I
	DVD-ROM, (16xDVD; 48xCD), half height, SATA I
	DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
	DVD Super Multi ultra slim , (8x DVD; 24x CD), ultraslim, SATA I
Hard disk drives	HDD SATA, 6 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical

Hard disk drives

HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 18 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 16 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 14 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 12 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 10 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 8 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, enterprise, SED
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 4 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 3.5-inch, enterprise
HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical

PCIe SSD & SATA DOM SSD	PCIe-SSD SFF, 960 GB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 800 GB, Write-Intensive, hot-plug, 2.5-inch, Flash drive, 100 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 400 GB, Write-Intensive, hot-plug, 2.5-inch, Flash drive, 100 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 15.36 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 12.8 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 7.68 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 6.4 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 1.0 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, Flash drive, 100 DWPD (Drive Writes Per Day for 5 years)
	PCIe-SSD SFF, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD (Drive Writes Per Day for 5 years)
SCSI / SAS Controller	PSAS CP 2100-8i LP SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
	Broadcom® PSAS CP600i LP SAS Ctrl. 12 Gbit/s PCIe 3.0 x8
	Broadcom® PSAS CP600e LP SAS Ctrl. 12 Gbit/s PCIe 3.0 x8
	Broadcom® PSAS CP600e FH SAS Ctrl. 12 Gbit/s PCIe 3.0 x8
RAID Controller	Fujitsu PRAID EP680i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 16 GT/s, 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3916
	Fujitsu PRAID EP680i FH, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 16 GT/s, 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3916
	Fujitsu PRAID EP680e LP, RAID 5/6 Ctrl., SAS 12 Gbit/s, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP680e FH, RAID 5/6 Ctrl., SAS 12 Gbit/s, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP640i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3908
	Fujitsu PRAID EP 3258-16i LP, RAID 5/6 Ctrl., SAS/SATA 24 Gbit/s, NVMe-PCIe 16 GT/s, 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU
	Fujitsu PRAID EP 3258-16i FH, RAID 5/6 Ctrl., SAS/SATA 24 Gbit/s, NVMe-PCIe 16 GT/s, 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU
	Fujitsu PRAID EP 3254-8i LP, RAID 5/6 Ctrl., SAS/SATA 24 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU
	Fujitsu PRAID EP 3252-8i LP, RAID 5/6 Ctrl., SAS/SATA 24 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU
	Broadcom® PRAID CP600i LP, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, No FBU support
Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Emulex LPE35000-M2-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPE35002-M2-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x Emulex LPE36000-M64-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x Emulex LPE36002-M64-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x Emulex LPE36000-M64-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe31000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style

GPU computing card	NVIDIA® A100 80GB, 6912 cores, 1935GB/s, 80GB HBM2e, N/A, PCIe 4.0 x16 -, N/A, - NVIDIA® A40, 48 GB, 696 GB/s, 48GB GDDR6, N/A, PCIe 4.0 x16 NVIDIA® RTX™ A6000, 48 GB, 786 GB/s, 48 GB GDDR6, N/A, PCIe 4.0 x16, 4 x DisplayPort NVIDIA® A16, 64 GB, 800GB/s (4 x200GB/s), 64GB GDDR6 (4 x16GB), N/A, PCIe 4.0 x16 NVIDIA® A30, 933GB/s, 24GB HBM2, N/A, PCIe 4.0 x16 NVIDIA® RTX™ A4500, 640 GB/s, 20GB GDDR6, N/A, PCIe 4.0 x16, 4 x DisplayPort NVIDIA® A2, 200GB/s, 16GB, N/A, PCIe 4.0 x8 NVIDIA® T400 4GB, 4 GB, 384 cores, 4GB, N/A, PCIe x16, 3 x miniDP
Rack infrastructure	Rack Mount Kit Cable Arm 2U for PRIMECENTER- and 3rd-party racks
Warranty	
Warranty period	3 years
Warranty type	Onsite warranty Warranty conditions tbd
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM
Product Support - the perfect extension	
Support Pack Options	Globally available in major metropolitan areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)
Recommended Service	24x7 Onsite Service with 4h Onsite Response Time
Service Lifecycle	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	http://www.fujitsu.com/fts/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to Fujitsu PRIMERGY TX2550 M7, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY TX2550 M7, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

<http://www.fujitsu.com/global/products/computing/servers/primergy/tower/tx2550m7/index.html>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2023 Fujitsu LIMITED

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.